


Overview

Product information



15EDGKD-3.5-10020000105

Pluggable terminal blocks, Rated current: 12A. Rated voltage (III/2) : 250V, Cross section: 1.5mm², pitch: 3.5mm, Color: green, Contact surface : Tin

Product advantages

- Adapt to multi-type sockets, device design is highly flexible
- Keying requirements can be met
- Universal installation method, suitable for various situations

Product certification



Technical data

Product drawing

3D model

□

Connection capacity

| | |
|----------------------------------|------------------------|
| Conductor cross section solid | 0.2~1.5mm ² |
| Conductor cross section flexible | 0.2~1.5mm ² |
| AWG | 28~16AWG |
| Torque | 0.4N.m |
| Strip length | 9mm |

Electrical parameters UL

| | |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (C) | 300V |

| | |
|-------------------|------|
| Rated voltage (D) | 300V |
| Rated current (B) | 8A |
| Rated current (D) | 8A |
| Rated current (C) | 8A |

Electrical parameters IEC

| | |
|----------------------------|-------|
| Rated voltage | 250V |
| Rated current | 12A |
| Rated current(III/2) | 250V |
| Rated surge voltage(III/2) | 2.5KV |

Item properties

| | |
|----------------------|---------------------------|
| Connection direction | 0° |
| Connection method | Push-in spring connection |
| Pitch | 3.5mm |
| Number of potentials | 8 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|-----------------------------|---------------------------|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact point metal surface | tin-plated |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

Test Specification

IEC61984/ UL1059

Environmental data

Ambient temperature (operation)

-40°C~105°C

Accessories

Business data

Order number

10020000105

Packing unit

600

Minimum order quantity

30

Products weight (without packaging)

7.2996