


Overview

Product information



15EDGKNHBM-3.5-10020000434

Pluggable terminal blocks, Rated current: 13.5A. Rated voltage (III/2) : 160V, Cross section: 1.5mm², pitch: 3.5mm, Color: green, Contact surface : Tin

Product advantages

- Adapt to multi-type sockets, device design is highly flexible
- PUSH-IN connection technology, fast wiring
- High-density double row, compact structure

Product certification



Technical data

Product drawing

3D model

□

Connection capacity

Conductor cross section solid	0.2~1.5mm ²
Conductor cross section flexible	0.2~1.5mm ²
AWG	28~16AWG
Strip length	11mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	10A

Rated current (D)	10A
Rated current (C)	10A

Electrical parameters IEC

Rated voltage	160V
Rated current(III/3)	160V
Rated current	13.4A
Rated current(III/2)	160V
Rated current(II/2)	320V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Connection method	Push-in spring connection
Pitch	3.5mm
Number of potentials	20
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
---------------------	---------

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accessories

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	15EDG-PWI

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10020000434
Packing unit	215
Minimum order quantity	30
Products weight (without packaging)	15.11