

Overview

Product information



2CDGB-5.08-10030001050

Pluggable terminal blocks,Rated current:12A.Rated voltage $(\verb||||/2\verb||):320V,pitch:5.08mm,Color:green,Contact surface:Tin$

Product advantages

- $\ensuremath{\mbox{$\sc\sc{Z}$}}$ Adapt to multi-type plugs, device design is highly flexible
- ☑ Through-wall installation, free positioning

Product certification



- 1	ect	าท	ıcaı	l da	ta

Product drawing

3D model

Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated current	12A

Rated current(III/2)	320V
Rated surge voltage(III/2)	2KV
em properties	
Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5.08mm
Number of potentials	11
Pluggable or not	Yes
Number of rows	1
aterial data	
Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0
lechanical tests	
Test Specification	IEC61984/ UL1059
nvironmental data	
Ambient temperature (operation)	-40℃~105℃

Acc	cessories		
Т	ool		
	Screwdriver	1	

Operating tool	1	
ccessories		
Coding strip	1	
Bridge	1	
Marking strip	1	
Others	2EDG-PWP-01H	

Business data		
Order number	10030001050	
Packing unit	210	
Minimum order quantity	30	
Products weight (without packaging)	10.119	