

Overview

Product information



2EDG-DBM-5.08-10010000846

Pluggable terminal blocks,Rated current:12A.Rated voltage (III/2):320V,pitch:5.08mm,Color:green,Contact surface:Tin

Product advantages

- $\ensuremath{\mbox{$\sc\sc{Z}$}}$ Adapt to multi-type plugs, device design is highly flexible
- ☑ Keying parts can be installed
- ☑ Universal installation method, suitable for various situations

Product certification



Technical data

Product drawing

3D model

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	28~12AWG
Torque	0.6N.m
Strip length	8mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A

Rated current (D) 10A	
-----------------------	--

Electrical parameters IEC

Rated voltage	320V
Rated current(III/3)	250V
Rated current	12A
Rated current(III/2)	320V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	10
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated

PA66
I
UL94V-0
IEC61984/ UL1059
-40℃~105℃

ool	
Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	1
ccessories	
Coding strip	2EDG-PWP
Bridge	DG019-5.0
Marking strip	1

Business data	
Order number	10010000846
Packing unit	160
Minimum order quantity	30
Products weight (without packaging)	22.1875