

#### Overview

#### **Product information**



# 2EDG-UDB-5.08-10010002843

Pluggable terminal blocks,Rated current:12A.Rated voltage (III/2):320V,pitch:5.08mm,Color:green,Contact surface:Tin

#### Product advantages

- $\ensuremath{\mbox{$\sc\sc{Z}$}}$  Adapt to multi-type plugs, device design is highly flexible
- ☑ Keying requirements can be met
- ☑ Din rail installation, suitable for various situations

Product certification



#### Technical data

DI	4 _	l
Prog	HCT C	Irawing

3D model

### Processing notes

Process Wave soldering/manua	al soldering
------------------------------	--------------

### Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	28~12AWG
Torque	0.6N.m
Strip length	7mm

## Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

## Electrical parameters IEC

Rated voltage	320V
Rated current(III/3)	250V
Rated current	12A
Rated current(III/2)	320V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

## Item properties

Connection direction	0°
Type of installation	Rail mounting
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	МЗ
Pitch	5.08mm
Number of potentials	9
Pluggable or not	Yes
Number of rows	1

### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

pol	
Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	I I
ccessories	
Coding strip	2EDG-PWP
Bridge	1
Bridge	
Marking strip	1

Business data	
Order number	10010002843
Packing unit	70

Minimum order quantity	30
Products weight (without packaging)	27.5