


## Overview

### Product information



## 2EDG-UDB-5.08-10010004390

Pluggable terminal blocks, Rated current: 12A, Rated voltage (III/2) : 320V, pitch: 5.08mm, Color: green, Contact surface : Tin

### Product advantages

- Adapt to multi-type plugs, device design is highly flexible
- Keying requirements can be met
- Din rail installation, suitable for various situations

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

Conductor cross section solid

0.2~2.5mm<sup>2</sup>

Conductor cross section flexible

0.2~2.5mm<sup>2</sup>

AWG

28~12AWG

Torque

0.6N.m

Strip length

7mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

#### Electrical parameters IEC

Rated voltage	320V
Rated current(III/3)	250V
Rated current	12A
Rated current(III/2)	320V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

#### Item properties

Connection direction	0°
Type of installation	Rail mounting
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	11
Pluggable or not	Yes
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

#### Accessories

##### Tool

Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	/

##### Accessories

Coding strip	2EDG-PWP
Bridge	/
Marking strip	/
Others	/

#### Business data

Order number	10010004390
Packing unit	50

Minimum order quantity	30
Products weight (without packaging)	36