


Overview

Product information



2EDGV-5.0-10030002127

Pluggable terminal blocks, Rated current: 20A, Rated voltage (II/2) : 320V, pitch: 5.0mm, Color: green, Contact surface : Tin

Product advantages

- Universal installation method to ensure a high degree of flexibility in device design
- The plug direction is parallel to the PCB

Product certification



Technical data

Product drawing

3D model

□

Processing notes

| | |
|---------|---------------------------------|
| Process | Wave soldering/manual soldering |
|---------|---------------------------------|

Electrical parameters UL

| | |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 15A |
| Rated current (D) | 10A |

Electrical parameters IEC

| | |
|---------------|------|
| Rated voltage | 320V |
| Rated current | 20A |

| | |
|----------------------------|------|
| Rated current(III/2) | 320V |
| Rated surge voltage(III/2) | 4KV |

Item properties

| | |
|----------------------|-------------------------------|
| Connection direction | 90° |
| Type of installation | PCB welding |
| Pin arrangement | Single row in a straight line |
| Pitch | 5mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|----------------------------|---------------------------|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact zone metal surface | tin-plated |
| Insulation Materials | PA66 |
| Shell color | green |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

| | |
|---------------------------------|-------------|
| Ambient temperature (operation) | -40°C~105°C |
|---------------------------------|-------------|

Accessories

Tool

| | |
|----------------|---|
| Screwdriver | / |
| Operating tool | / |

Accessories

| | |
|---------------|-----------------|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | 2EDG-PWP-01A(H) |

Business data

| | |
|-------------------------------------|-------------|
| Order number | 10030002127 |
| Packing unit | 200 |
| Minimum order quantity | |
| Products weight (without packaging) | 0.76 |