

Overview		
Product information		
	2EDGVC-5.0-10030002309 Pluggable terminal blocks,Rated current:20A.Rated voltage (III/2) :320V,pitch:5.0mm,Color:green,Contact surface :Tin	
Product advantages		
 Universal installation method to er The plug direction is perpendicula 		xibility in device design
Product certification		
Technical data		
Product drawing		
3D model		
٥		
Processing notes		
Process		Wave soldering/manual soldering
Electrical parameters UL		
Rated voltage (B)		300V
Rated voltage (D)		300V
Rated current (B)		15A
Rated current (D)		10A
Electrical parameters IEC		
Rated voltage		320V
Rated current		20A

Rated current(III/2)	320V
Rated surge voltage(III/2)	4KV
m properties	
Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5mm
Number of potentials	9
Pluggable or not	Yes
Number of rows	1
aterial data	
Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	Ι
Flammability rating	UL94V-0
echanical tests	
Test Specification	IEC61984/ UL1059
nvironmental data	
Ambient temperature (operation)	-40°C~105℃

Accessories	
Tool	
Screwdriver	/

Operating tool	1	
Accessories		
Coding strip	1	
Bridge	1	
Marking strip		
Others	2EDG-PWP-01H	

Business data	
Order number	10030002309
Packing unit	670
Minimum order quantity	30
Products weight (without packaging)	3.35