


## Overview

### Product information



## 8EDGCM-5.0-10020002856

Pluggable terminal blocks, Rated current:20A, Rated voltage (III/3) :320V, pitch:5.0mm, Color:gray, Contact surface :Tin

### Product advantages

- PCB welding, plug direction is parallel to the PCB
- Provides anti-touch protection for connection

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Connection capacity

Strip length

6mm

### Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

15A

Rated current (D)

10A

### Electrical parameters IEC

Rated voltage

320V

Rated current(III/3)

320V

Rated current	20A
Rated surge voltage(III/3)	4KV

#### Item properties

Connection direction	0°
Connection method	spring-cage connection
Pitch	5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

#### Accessories

##### Accessories

Coding strip	/
--------------	---

Bridge	/
Marking strip	/
Others	/

**Tool**

Operating tool	/
Screwdriver	/

**Business data**

Order number	10020002856
Packing unit	360
Minimum order quantity	30
Products weight (without packaging)	4.3