


## Overview

### Product information



## 8EDGKR-5.08-10020001428

Pluggable terminal blocks, Rated current: 20A, Rated voltage (III/2) : 320V, pitch: 5.08mm, Color: gray, Contact surface : Tin

### Product advantages

- Adapt to multi-type plugs, device design is highly flexible
- Cage clamp connection technology, fast wiring
- Universal installation method, suitable for various situations

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Connection capacity

Conductor cross section solid	0.2~2.5mm <sup>2</sup>
Conductor cross section flexible	0.2~2.5mm <sup>2</sup>
AWG	22~14AWG
Strip length	10mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A

Rated current (D)	10A
-------------------	-----

#### Electrical parameters IEC

Rated voltage	320V
Rated current	20A
Rated current(III/2)	320V
Rated surge voltage(III/2)	4KV

#### Item properties

Connection direction	0°
Pin arrangement	Single row in a straight line
Connection method	spring-cage connection
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

#### Environmental data

Ambient temperature (operation)

-40°C~105°C

#### Accessories

##### Tool

Screwdriver

/

Operating tool

DG010

##### Accessories

Coding strip

/

Bridge

DG018-5.0

Marking strip

/

Others

/

#### Business data

Order number

10020001428

Packing unit

100

Minimum order quantity

30

Products weight (without packaging)

3.5