

Overview

Product information



D10B-BK-2L-21010000012

10B Lower base, double button, no back cover

Product advantages

- Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- Various installation methods and outlet directions to meet on-site wiring requirements;
- Snap-in combination structure, dustproof, waterproof, easy operation;

Product certification

Technical data

Product drawing

3D model

□

Marking

| | |
|----------------|--------------------|
| classification | Upper Housing/base |
| Series | B |
| Type | Hole mounting base |
| Specification | Low structure |

versions

| | |
|------------------|-------------|
| Dimension | 10B |
| locking Category | Double lock |

Material characteristics

| | |
|---------------------|-----|
| Flammability rating | V-0 |
|---------------------|-----|

| | |
|-------------------------------|--------------------------|
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey (RAL 7037) |
| Material (seal) | NBR |
| Material (lock catch) | Zinc plated |

Technical specification

| | |
|-----------------------|--------------|
| Limiting temperatures | -40°C~+125°C |
| IP class | IP65 |

Accessories

Business data

| | |
|-------------------------------------|------------|
| Order number | 2101000012 |
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 128 |