

## Overview

### Product information



**D24B-BK-1L-21010000083**

24B Lower base, single buckle, no back cover

### Product advantages

- ☑ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑ Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑ Snap-in combination structure, dustproof, waterproof, easy operation;

### Product certification

## Technical data

### Product drawing

### 3D model

□

### Marking

|                |                    |
|----------------|--------------------|
| classification | Upper Housing/base |
| Series         | B                  |
| Type           | Hole mounting base |
| Specification  | Low structure      |

### versions

|                  |             |
|------------------|-------------|
| Dimension        | 24B         |
| locking Category | Single lock |

### Material characteristics

|                     |     |
|---------------------|-----|
| Flammability rating | V-0 |
|---------------------|-----|

|                               |                          |
|-------------------------------|--------------------------|
| RoHS                          | conform                  |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base)  | spray                    |
| Color (upper housing/base)    | Grey (RAL 7037)          |
| Material (seal)               | NBR                      |
| Material (lock catch)         | Zinc plated              |

#### Technical specification

|                       |              |
|-----------------------|--------------|
| Limiting temperatures | -40°C~+125°C |
| IP class              | IP65         |

#### Accessories

#### Business data

|                                     |            |
|-------------------------------------|------------|
| Order number                        | 2101000083 |
| Packing unit                        | 100        |
| Minimum order quantity              | 1          |
| Products weight (without packaging) | 146.7      |