

## Overview

### Product information



**D3A-BK-1L-MCV-21010000119**

3A Lower base, single buckle, no back cover, Wear protective cover

### Product advantages

- Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- Various installation methods and outlet directions to meet on-site wiring requirements;
- Snap-in combination structure, dustproof, waterproof, easy operation;

### Product certification

## Technical data

### Product drawing

### 3D model

□

### Marking

|                |                       |
|----------------|-----------------------|
| classification | Upper Housing/base    |
| Series         | A                     |
| Type           | Hole mounting base    |
| Description    | With metal dust cover |
| Specification  | Low structure         |

### versions

|                  |             |
|------------------|-------------|
| Dimension        | 3A          |
| locking Category | Single lock |

### Material characteristics

|                               |                     |
|-------------------------------|---------------------|
| Flammability rating           | V-0                 |
| RoHS                          | conform             |
| Material (upper housing/base) | Die-cast zinc alloy |
| Material(upper housing/base)  | spray               |
| Color (upper housing/base)    | Grey (RAL 7037)     |
| Material (seal)               | NBR                 |
| Material (lock catch)         | Stainless steel     |

#### Technical specification

|                       |              |
|-----------------------|--------------|
| Limiting temperatures | -40°C~+125°C |
| IP class              | IP65         |

#### Accessories

#### Business data

|                                     |             |
|-------------------------------------|-------------|
| Order number                        | 21010000119 |
| Packing unit                        | 100         |
| Minimum order quantity              | 1           |
| Products weight (without packaging) | 59          |