

Overview

Product information



DG103-5.0-10040000022

PCB terminal blocks,Rated current:24A,Rated voltage (III/2) 250V,Cross section:0.2-2.5mm²,pitch:5.0mm,connector method:Screw connector with tension sleeve,Color:green,Contact surface:Tin

Product advantages

- $\ensuremath{\square}$ Universal installation method to ensure a high degree of flexibility in device design
- ☑ 45° connection can realize multi-row layout on PCB
- ☑ Different poles can be combined through the side lock

Product certification





Technical data

drawing

3D model

Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	24~12AWG
Torque	0.5N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	24A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66

Insulating material group	I
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40°C~105°C

ccessories	
Coding strip	I I
Bridge	DG019-5.0
Marking strip	1
Others	/
ool	
Operating tool	1
Screwdriver	0.6x3.5mm, Slotted screwdriver

Business data	
Order number	10040000022
Packing unit	250
Minimum order quantity	30
Products weight (without packaging)	4.4