


## Overview

### Product information



## DG126R-5.0-10050000075

PCB terminal blocks, Rated current: 18A, Rated voltage (III/2) 250V, Cross section: 2.5mm<sup>2</sup>, pitch: 5.0mm, connector method: screw connector with wire protection, Color: green, Contact surface : Tin

### Product advantages

- Universal installation method to ensure a high degree of flexibility in device design
- Square wiring hole, large wiring capacity
- Different poles can be combined through the side lock

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

Conductor cross section solid

0.75~1.5mm<sup>2</sup>

Conductor cross section flexible

0.75~1.5mm<sup>2</sup>

AWG

26~14AWG

Strip length

7mm

### Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)	10A
-------------------	-----

#### Electrical parameters IEC

Rated voltage	250V
Rated current	10A
Rated current(III/2)	250V
Rated power frequency voltage(1min)	2KV

#### Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection with wire protection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	5mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

#### Accessories

##### Accessories

Coding strip	/
Bridge	DG019-5.0
Marking strip	/
Others	/

##### Tool

Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

#### Business data

Order number	10050000075
Packing unit	350
Minimum order quantity	30
Products weight (without packaging)	2.3956