


## Overview

### Product information



## DG127S-5.08-10040001492

PCB terminal blocks, Rated current: 15A, Rated voltage (III/2) 250V, Cross section: 0.2-1.5mm<sup>2</sup>, pitch: 5.08mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

### Product advantages

- Universal installation method to ensure a high degree of flexibility in device design
- 45° connection can realize multi-row layout on PCB
- Different poles can be combined through the side lock

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

### Connection capacity

Conductor cross section solid	0.2~1.5mm <sup>2</sup>
Conductor cross section flexible	0.2~1.5mm <sup>2</sup>
AWG	26~14AWG
Torque	0.4N.m
Strip length	6mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	12A
Rated current (D)	10A

#### Electrical parameters IEC

Rated voltage	250V
Rated current	15A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

#### Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	5.08mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66

Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

### Accessories

#### Accessories

Coding strip	/
Bridge	DG019-5.0
Marking strip	/
Others	/

#### Tool

Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

### Business data

Order number	10040001492
Packing unit	300
Minimum order quantity	30
Products weight (without packaging)	2.603