

#### Overview

#### **Product information**



# DG136T-10.16-10040001991

PCB terminal blocks,Rated current: 65A,Rated voltage (III/2) 1000V,Cross section:2.5-16mm²,pitch:10.16mm,connector method:Screw connector with tension sleeve,Color:green,Contact surface:Tin

### Product advantages

- $\ensuremath{\square}$  Universal installation method to ensure a high degree of flexibility in device design
- ☑ Different poles can be combined through the side lock

#### Product certification





#### Technical data

Product	uraviriy

3D model

#### Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

### Connection capacity

Conductor cross section solid	2.5~16mm²
Conductor cross section flexible	2.5~16mm²
AWG	20~6AWG
Torque	1.2N.m
Strip length	10mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	300V
Rated current (B)	60A
Rated current (D)	10A
Rated current (C)	60A

# Electrical parameters IEC

Rated voltage	1000V
Rated current	65A
Rated current(III/2)	1000V
Rated power frequency voltage(1min)	3.5KV

# Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-rowin a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	10.16mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

# Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper

Contact point metal surface	tin-plated		
Insulation Materials	PA66		
Insulating material group	I		
Flammability rating	UL94V-0		
Mechanical tests			
Test Specification	UL1059/IEC60998		
Environmental data			
Ambient temperature (operation)	-40℃~105℃		

ccessories	
Coding strip	
Bridge	1
Marking strip	1
Others	1
ool	
Operating tool	
Screwdriver	0.6x3.5mm, Slotted screwdriver

usiness data	
Order number	10040001991
Packing unit	70
Minimum order quantity	30
Products weight (without packaging)	23.33