

Overview

Product information



DG141V-2.54-10060000426

PCB spring terminal blocks, Rated current:6A, Rated voltage (III/2) :130V, pitch:2.54mm, Color:green, Contact surface :Tin

Product advantages

- PUSH-IN connection technology, fast wiring
- Different poles can be combined through the side lock
- Universal installation method to ensure a high degree of flexibility in device design

Product certification



Technical data

Product drawing

3D model

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~1.0mm²

Conductor cross section flexible

0.2~1.0mm²

AWG

24~20AWG

Strip length

11mm

Electrical parameters UL

Rated voltage (B)

150V

Rated voltage (C)

150V

| | |
|-------------------|------|
| Rated voltage (D) | 150V |
| Rated current (B) | 2A |
| Rated current (D) | 2A |
| Rated current (C) | 2A |

Electrical parameters IEC

| | |
|-------------------------------------|--------|
| Rated voltage | 130V |
| Rated current | 6A |
| Rated current(III/2) | 130V |
| Rated power frequency voltage(1min) | 1.25KV |

Item properties

| | |
|----------------------|-------------------------------|
| Connection direction | 90° |
| Type of installation | PCB welding |
| Pin arrangement | Double-row in a straight line |
| Connection method | Push-in spring connection |
| Pitch | 2.54mm |
| Number of potentials | 1 |
| Pluggable or not | no |
| Number of rows | 1 |

Material data

| | |
|-----------------------------|---------------------------|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact point metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |

| | |
|---------------------|---------|
| Flammability rating | UL94V-0 |
|---------------------|---------|

Mechanical tests

| | |
|--------------------|-----------------|
| Test Specification | UL1059/IEC60998 |
|--------------------|-----------------|

Environmental data

| | |
|---------------------------------|-------------|
| Ambient temperature (operation) | -40°C~105°C |
|---------------------------------|-------------|

Accessories

Accessories

| | |
|---------------|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

Tool

| | |
|----------------|---|
| Operating tool | / |
| Screwdriver | / |

Business data

| | |
|-------------------------------------|-------------|
| Order number | 10060000426 |
| Packing unit | 500 |
| Minimum order quantity | 30 |
| Products weight (without packaging) | 0.81 |