

Overview

Product information



DG167-5.0-10030003093

PCB terminal blocks,Rated current:22A,Rated voltage (III/2) 250V,Cross section:2.5mm²,pitch:5.0mm,connector method:screw connector with wire protection,Color:green,Contact surface :Tin

Product advantages

- $\ensuremath{\square}$ Fixed screw connection technology,safe and reliable
- ☑ Square wiring hole,large wiring capacity
- $\ensuremath{\square}$ Universal installation method to ensure a high degree of flexibility in device design

Product certification



Rated voltage (B)

Wave soldering/manual soldering
0.5~2.5mm²
0.5~2.5mm²
22~12AWG
7mm

300V

Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	22A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection with wire protection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	5mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40℃~105℃

ool	
Screwdriver	0.6x3.5mm, Slotted screwdriver
Operating tool	
ccessories	
Coding strip	
Bridge	DG019-5.0
Marking strip	1
Others	

usiness data	
Order number	10030003093
Packing unit	#N/A
Minimum order quantity	30
Products weight (without packaging)	#N/A