


Overview

Product information



DG2002-4.0-300A(H)-10060001737

PCB spring terminal blocks, Rated current:9A, Rated voltage (III/2) :160V, pitch:4.0mm, Color:White, Contact surface :Tin

Product advantages

- PUSH-IN connection technology, fast wiring
- Suitable for SMT welding process
- Compact structure, saving installation space

Product certification



Technical data

Product drawing

3D model

□

Electrical parameters UL

Rated current (B)

9A

Electrical parameters IEC

Rated voltage

160V

Rated current(III/3)

32V

Rated current

9A

Rated current(III/2)

160V

Rated current(II/2)

160V

Rated surge voltage(III/3)

4KV

Rated surge voltage(III/2)

4KV

Rated surge voltage(II/2)	4KV
---------------------------	-----

Item properties

Connection direction	0°
Pitch	4mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1977
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~130°C
---------------------------------	-------------

Accessories

Accessories

Coding strip	/
Bridge	DG027-4.0
Marking strip	/
Others	/

Tool

Operating tool	DG028
----------------	-------

Screwdriver

/

Business data

Order number	10060001737
Packing unit	0
Minimum order quantity	30
Products weight (without packaging)	1