


Overview

Product information



DG238-10.0-10060000994

PCB spring terminal blocks, Rated current:24A. Rated voltage (III/2) :450V, pitch:10.0mm, Color:White, Contact surface :Tin

Product advantages

- Multiple wiring holes for current distribution
- Panel mounting, suitable for various situations
- Can realize horizontal wire-to-wire connection

Product certification



Technical data

Product drawing

3D model

□

Connection capacity

AWG	22~14AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	600V
Rated current (B)	20A

Electrical parameters IEC

Rated current	450V
	24A
Rated current(III/2)	450V

Rated power frequency voltage(1min)	2.5KV
-------------------------------------	-------

Item properties

Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accessories

Accessories

Coding strip	/
Bridge	/
Marking strip	/

Others	/
--------	---

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10060000994
Packing unit	50
Minimum order quantity	30
Products weight (without packaging)	9.2