


## Overview

### Product information



## DG238-10.0-10060000994

PCB spring terminal blocks, Rated current:24A. Rated voltage (III/2) :450V, pitch:10.0mm, Color:White, Contact surface :Tin

### Product advantages

- Multiple wiring holes for current distribution
- Panel mounting, suitable for various situations
- Can realize horizontal wire-to-wire connection

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Connection capacity

AWG	22~14AWG
Strip length	9mm

### Electrical parameters UL

Rated voltage (B)	600V
Rated current (B)	20A

### Electrical parameters IEC

Rated current	450V
	24A
Rated current(III/2)	450V

Rated power frequency voltage(1min)	2.5KV
-------------------------------------	-------

#### Item properties

Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-2

#### Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

#### Accessories

##### Accessories

Coding strip	/
Bridge	/
Marking strip	/

Others	/
--------	---

**Tool**

Operating tool	/
Screwdriver	/

**Business data**

Order number	10060000994
Packing unit	50
Minimum order quantity	30
Products weight (without packaging)	9.2