


## Overview

### Product information



## DG250-3.5 reverse pin pattern-10060002967

PCB spring terminal blocks, Rated current: 10A. Rated voltage (III/2) : 320V, pitch: 3.5mm, Color: gray, Contact surface : Tin

### Product advantages

- PUSH-IN connection technology, fast wiring
- 45° connection can realize multi-row layout on PCB
- Universal installation method, suitable for various situations

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

Conductor cross section solid

0.2~1.5mm<sup>2</sup>

Conductor cross section flexible

0.2~1.5mm<sup>2</sup>

AWG

22~16AWG

Strip length

9mm

### Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (C)

150V

Rated voltage (D)	300V
Rated current (B)	8A
Rated current (D)	8A
Rated current (C)	8A

#### Electrical parameters IEC

Rated voltage	320V
Rated current(III/3)	320V
Rated current	10A
Rated current(III/2)	320V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

#### Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	Push-in spring connection
Pitch	3.5mm
Number of potentials	16
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
---------------------	---------------------------

Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

#### Accessories

##### Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

##### Tool

Operating tool	/
Screwdriver	/

#### Business data

Order number	10060002967
Packing unit	300
Minimum order quantity	30
Products weight (without packaging)	7.5

