

## Overview

### Product information



## DG340R-3.81-10050000290

PCB terminal blocks, Rated current: 10A, Rated voltage (III/2) 130V, Cross section: 1.0mm<sup>2</sup>, pitch: 3.81mm, connector method: screw connector with wire protection, Color: blue, Contact surface : Tin

### Product advantages

- Universal installation method to ensure a high degree of flexibility in device design
- Different poles can be combined through the side lock

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

### Connection capacity

Conductor cross section solid	0.5~1.0mm <sup>2</sup>
Conductor cross section flexible	0.5~1.0mm <sup>2</sup>
AWG	24~18AWG
Torque	0.2N.m
Strip length	5mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	7A

#### Electrical parameters IEC

Rated voltage	130V
Rated current	10A
Rated current(III/2)	130V
Rated power frequency voltage(1min)	1.25KV

#### Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection with wire protection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.81mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

**Mechanical tests**

Test Specification

UL1059/IEC60998

**Environmental data**

Ambient temperature (operation)

-40°C~105°C

**Accessories****Accessories**

Coding strip

/

Bridge

DG032-3.81

Marking strip

/

Others

/

**Tool**

Operating tool

/

Screwdriver

0.3x2.0mm, Slotted screwdriver

**Business data**

Order number

10050000290

Packing unit

#N/A

Minimum order quantity

30

Products weight (without packaging)

#N/A