

## Overview

### Product information



## DG381S-3.5-10040002070

PCB terminal blocks, Rated current:10A, Rated voltage (III/2) 130V, Cross section:1.5mm<sup>2</sup>, pitch:3.5mm, connector method:Screw connector with tension sleeve, Color:green, Contact surface :Tin

### Product advantages

- Universal installation method to ensure a high degree of flexibility in device design
- 45° connection can realize multi-row layout on PCB
- Fixed screw connection technology, safe and reliable

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

### Connection capacity

Conductor cross section solid	0.2~1.5mm <sup>2</sup>
Conductor cross section flexible	0.2~1.5mm <sup>2</sup>
AWG	26~16AWG
Torque	0.2N.m
Strip length	6mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	10A

#### Electrical parameters IEC

Rated voltage	130V
Rated current	10A
Rated current(III/2)	130V
Rated power frequency voltage(1min)	1.25KV

#### Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

**Mechanical tests**

Test Specification

UL1059/IEC60998

**Environmental data**

Ambient temperature (operation)

-40°C~105°C

**Accessories****Accessories**

Coding strip

/

Bridge

/

Marking strip

/

Others

/

**Tool**

Operating tool

/

Screwdriver

0.4x2.5mm, Slotted screwdriver

**Business data**

Order number

10040002070

Packing unit

500

Minimum order quantity

30

Products weight (without packaging)

1.25