

## Overview

## Product information


**DG48H-A-12040000159**

Single-layer PCB barrier terminal blocks, Rated current:20A. Rated voltage (UL) :300V, Cross section:22~12AWG, pitch:9.5mm, Color:black, Contact surface:Tin

## Product advantages

- Screw connection for worldwide use
- Fence type wiring structure, stable and reliable connection
- Solder plate mounting for electrical connection of the device to the PCB

## Product certification



## Technical data

## Product drawing

## 3D model

## Processing notes

Process

Wave soldering/manual soldering

## Connection capacity

AWG

22~12AWG

Torque

1.2N.m

## Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (C)

150V

Rated voltage (D)

300V

Rated current (B)	20A
Rated current (D)	10A
Rated current (C)	20A

#### Electrical parameters IEC

Rated current	600V
	32A

#### Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M4
Pitch	9.5mm
Number of potentials	10
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	II
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	UL1059
--------------------	--------

#### Environmental data

Ambient temperature (operation)

-40°C~105°C

#### Accessories

##### Accessories

Bridge

K24

#### Business data

Order number

12040000159

Packing unit

100

Minimum order quantity

/

Products weight (without packaging)

42