

#### Overview

#### **Product information**



# DG503-5.08-10040000532

PCB terminal blocks,Rated current: 20A,Rated voltage (III/2) 450V,Cross section:0.2-2.5mm²,pitch:5.08mm,connector method:Screw connector with tension sleeve,Color:green,Contact surface :Tin

#### Product advantages

- $\ensuremath{\square}$  Fixed screw connection technology,safe and reliable
- $\ensuremath{\square}$  Different poles can be combined through the side lock
- ☑ Universal installation method to ensure a high degree of flexibility in device design

#### Product certification





#### Technical data

Prod	uct	dra	wina
1 100	uoi	uı u	WILLIA

3D model

#### Processing notes

Process	Wave soldering/manual soldering
---------	---------------------------------

### Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	28~12AWG
Torque	0.5N.m
Strip length	7mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

# Electrical parameters IEC

Rated voltage	450V
Rated current	20A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

### Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	МЗ
Pitch	5.08mm
Number of potentials	4
Pluggable or not	no
Number of rows	1

# Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66

Insulating material group	I
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40℃~105℃

ccessories	
Coding strip	I
Bridge	DG019-5.0
Marking strip	
Others	
ool	
Operating tool	1
Screwdriver	0.6x3.5mm, Slotted screwdriver

usiness data	
Order number	10040000532
Packing unit	1200
Minimum order quantity	30
Products weight (without packaging)	6.068