

## Overview

## Product information


**DG89-A-12050000061**

Transfer barrier terminal blocks, Rated current:30A. Rated voltage (UL) :300V, Cross section:22~10AWG, pitch:14.00mm, Color:black, Contact surface: Tin

## Product advantages

- Screw connection for worldwide use
- Fence type wiring structure, stable and reliable connection
- Panel mounting for electrical transfer between two devices in a small space

## Product certification



## Technical data

## Product drawing

## 3D model

## Connection capacity

AWG	22~10AWG
Torque	1.2N.m

## Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	600V
Rated current (B)	30A
Rated current (D)	5A

Rated current (C)	30A
-------------------	-----

Electrical parameters IEC

Rated current	1000V
	41A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M4
Pitch	14mm
Number of potentials	16
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

## Accessories

### Accessories

--	--

## Business data

Order number	12050000061
Packing unit	35
Minimum order quantity	/
Products weight (without packaging)	121.4