

## Overview

### Product information



## DGR150-20A(H)-12010000100

Transfer barrier terminal blocks, Rated current:155A. Rated voltage (UL) :600V, Cross section:20~2/0AWG, pitch:27mm, Color:black, Contact surface:Tin

### Product advantages

- Screw connection for worldwide use
- Fence type wiring structure, stable and reliable connection
- Provide the cabinet and panel electrical transfer connections

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Connection capacity

AWG	20~2/0AWG
-----	-----------

### Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	150A
Rated current (C)	150A

### Electrical parameters IEC

Rated current	1000V
---------------	-------

**Item properties**

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M8
Pitch	27mm
Number of potentials	4
Pluggable or not	no
Number of rows	1

**Material data**

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

**Mechanical tests**

Test Specification	UL1059
--------------------	--------

**Environmental data**

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

**Accessories**

Accessories

Business data

Order number	12010000100
Packing unit	1
Minimum order quantity	/
Products weight (without packaging)	349.6