

## Overview

## Product information


**DGR150-00A(H)-12010000091**

Transfer barrier terminal blocks, Rated current: 155A. Rated voltage (UL) : 600V, Cross section: 20~2/0AWG, pitch: 27mm, Color: black, Contact surface: Tin

## Product advantages

- Screw connection for worldwide use
- Fence type wiring structure, stable and reliable connection
- Provide the cabinet and panel electrical transfer connections

## Product certification



## Technical data

## Product drawing

## 3D model

## Connection capacity

AWG

20~2/0AWG

## Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (C)

600V

Rated voltage (D)

600V

Rated current (B)

150A

Rated current (C)

150A

## Electrical parameters IEC

Rated current	1000V
---------------	-------

**Item properties**

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M8
Pitch	27mm
Number of potentials	10
Pluggable or not	no
Number of rows	1

**Material data**

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

**Mechanical tests**

Test Specification	UL1059
--------------------	--------

**Environmental data**

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

**Accessories**

Accessories

Business data

Order number	12010000091
Packing unit	1
Minimum order quantity	/
Products weight (without packaging)	1085.3