


## Overview

## Product information

**DGR60-20A(H)-12010000184**

Transfer barrier terminal blocks, Rated current: 80A. Rated voltage (UL) : 600V, Cross section: 20~4AWG, pitch: 19mm, Color: black, Contact surface: Tin

## Product advantages

- Screw connection for worldwide use
- Fence type wiring structure, stable and reliable connection
- Provide the cabinet and panel electrical transfer connections

## Product certification



## Technical data

## Product drawing

## 3D model

□

## Connection capacity

AWG	20~4AWG
-----	---------

## Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	80A
Rated current (D)	5A

## Electrical parameters IEC

Rated current	1000V
	101A

#### Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M6
Pitch	19mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	UL1059
--------------------	--------

#### Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

#### Accessories

Accessories

--	--

Business data

Order number	12010000184
Packing unit	3
Minimum order quantity	/
Products weight (without packaging)	175