


## Overview

## Product information


**DS16-PE-11040000070**

Push-in Din-Rail TB, connector method: Push-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.5 mm<sup>2</sup> - 25 mm<sup>2</sup>, AWG: 20 - 4, Width: 12.2 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

## Product advantages

- Push-in connection technology, tool-free operation, more convenient and faster;
- With orange wire button, one word or cross screwdriver can release wire.
- Optional marker to avoid wire mis-inserting.
- Equipped with test holes for easy testing of the circuit.

## Product certification



## Technical data

## Product drawing

## 3D model

## IEC Electrical parameters

Rated voltage (III / 3)	/
Rated current (III / 3)	/

## UL Electrical parameters

Rated voltage	/
Rated current	/

## Wiring data

Conductor cross section flexible (ferrule without plastic sleeve)	0.5-16mm <sup>2</sup>
---	-----------------------

Conductor cross section flexible (ferrule with plastic sleeve)	0.5-16mm <sup>2</sup>
2 flexible conductors with a TWIN ferrule	1.5-4mm <sup>2</sup>
Strip length	18mm
Conductor cross section solid	0.5~25mm <sup>2</sup>
Conductor cross section flexible	0.5~16mm <sup>2</sup>
Conductor cross section solid AWG	20~4

#### Environmental conditions

Ambient temperature (storage / transport)	-25°C~60°C
Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

#### IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

#### Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

#### Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

#### Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

#### Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

#### Dimension

NS 35/7,5 Height	53.3mm
End plate width	2.2mm
NS 35/15 Height	60.8mm
length	75.4mm
width	12.2mm
Height	45.8mm

#### Overview

Insulating material group	I
standard test	IEC60947-7-2
Connection type	In line connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

#### Accessories

##### Marker

Top marker	ZB10 / ZS12
Side marker	ZSF12
Marker support	DTH5-25x5 / DTH5-25x12

##### Accessories

Slotted screwdriver size (Blade thickness x Width) mm	1x5.5
Bridge	/
End cover	D-DS16

## Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

## Business data

Order number	11040000070
Packing unit	20
Minimum order quantity	20
Products weight (without packaging)	37.11