

## Overview

### Product information



## FBUS17.5-05P-10020001617

DIN rail bus connector, Number of potentials: 5, pitch: 3.81 mm, Color: light gray. Compatible housing: FMED-03P, FMEH-03P.

### Product advantages

- Modular design
- Multiple connection technologies optional, signal, data, and power transmission can be realized
- bus connector is optional
- Various personalized solutions can be achieved according to customer needs

### Product certification

## Technical data

### Product drawing

### 3D model

### Item properties

Pitch	3.81mm
Number of potentials	5
Type of installation(din rail \ panel \ PCB soldering)	din rail
Pluggable or not	Yes
Number of rows	1

### Material data

Environmental items(Compliant with REACH/RoHS )	Yes
Conductor material (copper / copper alloy)	Copper alloy
Contact point metal surface(conductor contact with wire)	gold

Contact zone metal surface(insert&pullout)	gold
Shell color	light gray
Insulation Materials (main class)	PA66
Insulating material group	I
Flammability rating	V0

#### Mechanical tests

Test standard (standard no.)	UL1059
------------------------------	--------

#### Durability test

Insert / pull out cycle	50
-------------------------	----

#### Electrical parameters

Rated current(B) UL	7A
	150V

#### Environmental data

Ambient temperature (operation)	-40℃ ~ +105℃
Ambient temperature (storage / transport)	-40℃ ~ +70℃

#### Accessories

##### Accessories

--	--

#### Business data

Order number	10020001617
Packing unit	90
Minimum order quantity	90
Products weight (without packaging)	3.89

