

## Overview

## Product information


**PM-M12A-04P-FF-SR8A01-20030000654**

Sensor/Actuator Cable,PVC,black,UL2517,Female plug,acodado M12,Coding A,Unshielded,Trimming cable end,Cable Cable length:1m

## Product advantages

- Sealing optimization, protection level up to IP68
- Meet the harsh environment
- Suitable for various occasions connection technology
- Compatible with the international and domestic same series products

## Product certification

**RoHS REACH**

## Technical data

## Product drawing

## 3D model

□

## Environmental conditions

|                     |              |
|---------------------|--------------|
| Ambient temperature | -25°C...85°C |
|---------------------|--------------|

|          |      |
|----------|------|
| IP class | IP68 |
|----------|------|

## General parameters

|               |      |
|---------------|------|
| Rated current | 4A   |
|               | 250V |

|                      |   |
|----------------------|---|
| Number of potentials | 4 |
|----------------------|---|

|                       |          |
|-----------------------|----------|
| Insulation resistance | ≥ 100 MΩ |
|-----------------------|----------|

|                    |        |
|--------------------|--------|
| Error-proof coding | A-Code |
|--------------------|--------|

|                             |        |
|-----------------------------|--------|
| Overvoltage level           | II     |
| Pollution level             | 3      |
| Insertion and pullout cycle | ≥ 100  |
| Torque                      | 0.4 Nm |

#### Material

|  |                           |
|--|---------------------------|
| Flammability rating ,in line with UL94 | V0                        |
| Flammability rating ,in line with UL97 | HB                        |
| Contact material                       | CuZn                      |
| Material contact surface               | Au                        |
| Contact carrier material               | PU                        |
| Fixture body material                  | TPU                       |
| Coil material                          | Zinc alloy, nickel plated |
| Sealing material                       | Silicon                   |

#### Standards and specifications

|                          |                 |
|--------------------------|-----------------|
| Standards/specifications | IEC 61076-2-101 |
|--------------------------|-----------------|

#### Cable

|  |                                |
|--|--------------------------------|
| Cable type                                 | PVC Black                      |
| Cable type(abbreviation)                   | PVC                            |
| UL AWM form                                | UL2517                         |
| Cross section                              | 0.34mm <sup>2</sup>            |
| AWG signal wire                            | 22AWG                          |
| Wire structure Signal wire                 | 17/0.16mm <sup>2</sup>         |
| Core diameter (including insulation layer) | 1.30±0.05mm                    |
| Wire color                                 | 1 Brown 2 White 3 Blue 4 Black |
| Thickness, insulation                      | 0.6mm                          |

|                               |                                      |
|-------------------------------|--------------------------------------|
| Cable outer diameter D        | 5.0 ±0.2mm                           |
| Outer sheath, material        | PVC                                  |
| Conductor insulation material | PVC                                  |
| Conductor material            | Tinned copper                        |
| Insulation resistance         | ≥100MΩ                               |
| Conductor resistance          | Maximum 59.4Ω/km (at 20 °C )         |
| Nominal cable voltage         | 300V                                 |
| Cable test voltage            | 2000V                                |
| Flame retardant               | Comply with UL 758/1581 FT1 standard |
| Halogen free                  | Yes                                  |

#### Dimension

|              |    |
|--------------|----|
| Cable length | 1m |
|--------------|----|

#### Accessories

##### Accessories

|             |                 |
|-------------|-----------------|
| Sealing cap | CAP-M12-MP-8001 |
|-------------|-----------------|

#### Business data

|                                     |             |
|-------------------------------------|-------------|
| Order number                        | 20030000654 |
| Packing unit                        | /           |
| Minimum order quantity              | 100         |
| Products weight (without packaging) | /           |