

## Overview

### Product information



## TSC6-10070000048

Transformer terminal blocks, Rated current:41A. Rated voltage (III/2) :750V, Color:Orange , Contact surface :Tin

### Product advantages

- Screw connection technology, safe and reliable
- Rail installation method, suitable for transformer wiring

### Product certification



## Technical data

### Product drawing

### 3D model

### Connection capacity

Conductor cross section solid	0.5~6mm <sup>2</sup>
Conductor cross section flexible	0.5~6.0mm <sup>2</sup>
AWG	20~10AWG
Torque	1.2N.m
Strip length	11mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated current (B)	20A

Rated current (C)	20A
-------------------	-----

Electrical parameters IEC

Rated current	750V
	41A
Rated current(III/2)	750V
Rated surge voltage(III/2)	2.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

## Accessories

### Accessories

Coding strip	TZB4
Bridge	/
Marking strip	/
Others	/

### Tool

Operating tool	/
Screwdriver	/

## Business data

Order number	10070000048
Packing unit	595
Minimum order quantity	30
Products weight (without packaging)	7.44