


## Overview

### Product information



## WS16-SD-11030000086

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 76 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 16 mm<sup>2</sup>, AWG: 24 - 6, Width: 12 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

### Product advantages

- spring-cage connection technology, good anti-vibration performance;
- Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- Unique plug-in bridge, high circuit connection efficiency;
- Can be matched with marker strips to avoid incorrect insertion of wires.

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Overview

Connection method	spring-cage connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
Insulating material group	I

standard test	IEC60947-7-1
---------------	--------------

#### Dimension

width	12mm
End plate width	4mm
Height	49.85mm
NS 35/7,5 Height	52.6mm
NS 35/15 Height	60.1mm
length	58.5mm

#### Wiring data

Strip length	16~17mm
Conductor cross section solid AWG	24~6
Conductor cross section solid	0.2~16mm <sup>2</sup>
Conductor cross section flexible	0.2~16mm <sup>2</sup>

#### IEC Electrical parameters

Rated voltage (III / 3)	800V
Rated current (III / 3)	76A
Rated surge voltage	8KV

#### UL Electrical parameters

Rated voltage	600V
Rated current	65A

#### Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%
Ambient temperature (storage / transport)	-25°C~60°C

#### Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

#### Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

#### Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

#### Environmental protection

RoHS	No excessive harmful substances
REACH SVHC	Lead 7439-92-1

### Accessories

#### Marker

Top marker	/
Side marker	ZT12 / WB5
Marker support	/
Warning cover	EEA16

#### Accessories

Slotted screwdriver size (Blade thickness x Width)	0.8×5.5
Adjacent jumper (2P)	WFA16
Alternate jumper (2P)	WFB16
Staggered jumper (2P)	/
End cover	D-WS16-SD

#### Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

#### Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

#### Accessories

End cover	D-WS16-SD
Bridge	WFA16
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

#### Business data

Order number	11030000086
Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	27.86